

# Q80

## RELIABLE Countertop



Food & Beverage



Fashion & Retail



Supermarkets



**CLASSIC**



Powered by  
Prolin



PCI 4  
SRED



4"  
Display













0.3MP  
Front



Advanced  
Connectivity

## SPECIFICATIONS

	<b>Operating System</b>	Prolin
	<b>Processor</b>	Cortex A9
	<b>Memory</b>	512MB FLASH + 512MB DDR RAM Extended microSD Card Slot Up To 32GB
	<b>Card Readers</b>	Chip & PIN   NFC Contactless   Magnetic Stripe
	<b>Cameras</b>	0.3MP Front-Facing (optional)
	<b>Display</b>	4" TFT WVGA 480 x 800 Pixels Touch Screen
	<b>Comms Configurations</b>	Wi-Fi® 2.4GHz/5GHz (optional)   4G (FDD-LTE) (optional) 3G (WCDMA) (optional)   <b>Bluetooth®</b> (optional)   Modem (optional)   LAN
	<b>Battery</b>	720mAh   7.4V (optional)
	<b>Printer</b>	50 lines/sec   Paper Roll Outer Diameter: 40mm/50mm
	<b>SIM / SAM</b>	3 Mini SAMs   1 Mini SIM + 2 Mini SAMs   2 Mini SIMs + 1 Mini SAM
	<b>Keys / Buttons</b>	15 Keys: 0~9   Menu   Func   Cancel   Clear   Enter
	<b>Audio</b>	1 Speaker
	<b>Ports</b>	1 RS232   1 Line   1 Phone   1 Ethernet   1 PINpad Port   1 micro-USB OTG   1 USB Host
	<b>Physical</b>	181 x 83 x 72mm, 410g (excluding battery) 181 x 84 x 81mm, 418g (excluding battery)
	<b>Environmental</b>	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	<b>Accessories</b>	PS200 Pole Stand (optional)   Privacy Shield (optional)   Cluster Cable (optional)   Back Up Battery (optional)
	<b>Certifications</b>	PCI PTS 4.x SRED   EMV L1 & L2   EMV Contactless L1   Visa payWave   Mastercard contactless   UPI qUICS   Amex Expresspay   Discover D-PAS   JCB J/Speedy   Interac Flash   Mastercard TQM   CE   RoHS

