

S920

Terminal Mobile



Restauration



Enseigne



Transport



CLASSIC



Prolin
Linux



PCI 4
SRED



Ecran
3.5"



Chargement
Rapide



Connectivité
Optimale

CARACTERISTIQUES

	OS	Prolin
	Processeur	ARM11
	Mémoire	128MB Flash + 64MB DDR RAM Extensible par Micro SD jusqu'à 32GB
	Lecteurs Cartes	Puce NFC Sans Contact Piste Magnetique
	Caméras	Non
	Ecran	3.5" TFT QVGA 240 * 320 Pixels Tactile
	Configurations de Communications	4G/3G/2G + WiFi (2.4GHz) + Bluetooth 4.2 3G/2G WiFi (2.4GHz) + Bluetooth 4.2
	Batterie	2600mAh 3.7V 3250mAh 3.7V (en option)
	Imprimante	30 Lignes/Sec Diamètre du rouleau de papier : 40mm (standard)
	SIM / SAM	1 SIM + 2 SAM 2 SIM+ 1 SAM (en option)
	Geolocalisation	GPS en option
	Touches / Boutons	15 Touches: 0~9 Fonctions Alpha Validation Annulation Correction
	Audio	1 Haut-Parleur
	Ports	1 Micro USB2.0 OTG
	Dimensions / Poids	165 * 78 * 56 mm, 365g (incluant la batterie)
	Environnement	-10°C ~ 50°C (14°F ~ 122°F) Température d'Utilisation -20°C ~ 70°C (-4°F ~ 158°F) Température de Stockage -10% ~ 93% Humidité relative, Sans condensation
	Accessoires	B920: Base Chargeur 1 Power Port 135 * 84 * 43 mm B920-B: Base + Communicante 1 RS232-A (RJ45) 1 RS232-B (RJ45) 1 Ethernet (RJ45) 1 PSTN (RJ11) 1 USB (host) 1 USB (device) 1 Power Port Bluetooth 135 * 84 * 43 mm
	Certifications	PCI PTS 4.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qUICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash MasterCard TQM Common.SECC UKCC CE RoHs FCC UL IC PTCRB APCA

