

S300 TRADITIONAL Smart PINpad



Supermarkets



Fashion & Retail



Food & Beverage













SPECIFICATIONS

oo	Operating System	Prolin/PaxMe
	Processor	32-bit ARM 11
	Memory	128MB Flash + 64MB DDR
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Display	3.5" TFT QVGA 240 x 320 Pixels Touch Screen
((†))	Comms Configurations	RS232 USB 2.0 Fast Ethernet
SAM	SIM / SAM	3 Micro SAMs
(F)	Keys / Buttons	15 Keys: Func 0 ~ 9 Alpha Enter Clear Cancel Back-Lighting
()))	Audio	1 Speaker
	Ports	Single Multi-Port Connector: 2 RS232 1 USB2.0 1 Fast Ethernet 1 Power
	Physical	167 x 81 x 50mm, 290g
Œ	Power Supply	External Power Supply 5V DC, 0.5A
Ö	Environmental	$0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ (32°F \sim 122°F) Operating Temperature -20°C \sim 70°C (-4°F \sim 158°F) Storage Temperature 10% \sim 93% Relative Humidity, Non-Condensing
(3)	Accessories	PS200 Pole Stand Multi-Function Cable
\bigcirc	Certifications	PCI PTS 4.x, SRED EMV L1 & L2 EMV Contactless L1 Visa payWave Mastercard contactless UPI qUICS American Expresspay Discover D-PAS JCB J/Speedy Interac Flash Mastercard TQM Common.SECC UKCC CE RoHs







